

USB Serial Adapter (F5U003)

The USB Serial Adapter will allow any Windows 98 PC equipped with a USB port to use any serial device through the port. It provides connectivity to new and existing RS-232 devices, thus providing perfect compatibility and easy functionality right out of the box. When used in conjunction with the Express Bus, up to 127 devices can be connected. An instruction manual, installation software and USB device cable are included in the package.



Features

- 100% compliant to USB specification, Rev. 1.1
- Connect up to 127 serial devices to your PC's USB port
- User friendly Plug-n-Play
- Perfect for, Serial printers, high-speed external modems, ISDN modems, digital cameras, scanners, input devices, and graphics tablets
- Software installs in seconds
- No IRQ, I/O address, DMA, or memory address requirements
- Supports serial devices including modems, ISDN terminal adapters, printers, PDAs and point of sale and industrial automation applications.
- Powered solely from USB Bus – no external power necessary
- Ideal for connection to 56K modems
- Save serial ports for use with other serial devices
- Windows 98 or Windows 95 (OSR2) compatible
- Eliminate manual or automatic serial switchboxes
- CE, FCC Class A and B Approved
- Supports speeds up to 115.2Kbps
- Includes six-foot USB device cable (F3U133-06)
- Lifetime warranty

Ordering Information

Product Name:	USB Serial Adapter
Part #:	F5U003
UPC Code:	7-22868-20830-4
Package Dimensions:	7 ^{1/2"} L x 2 ^{1/4"} W x 6"H 1 ^{3/4"} hang tab
Individual Ship Weight:	1 lb.
Case Pack Quantity & Dimensions:	4 per case pack 11" L x 7 ^{3/4"} W x 6 ^{1/4"} H
Package Contents:	USB Serial Adapter Installation Software Retail Box Instruction Manual USB cable (F3U133-06)



	Warranty Card
MSRP:	\$99.99



Product Specifications

USB Serial Adapter (F5U003)

Windows System Requirements	<ul style="list-style-type: none">• IBM Compatible PC with 486/66 or higher processor• Windows 98 or Windows 95 (OSR2)• Minimum 16 MB RAM• 30 MB of available hard disk space• USB Port or USB PCI Card
Standard:	Universal Serial Bus Specification, Rev. 1.1 OHCI and UHCI compliant RS-232C
Connectors:	(1) USB series B receptacle (1) DB9 male
Speed:	12Mbps and 1.5Mbps, USB 1200bps to 115.2 Kbps, Serial Port
LEDs:	(1) red LED for Power/Status (2) green LEDs for Activity
Power:	Bus Powered
Cable:	Includes F3U133-06 (6 ft)
Approvals:	FCC Class A and B, CE
Operating Environment:	0° C to 40 0°; 0 to 95% RH (non-condensing)